

DIRECT FIRED HEATERS



FOR CONSTRUCTION SITES

This heater series is engineered for simple operation and minimal servicing. The light and portable design is stackable for easy transportation and storage. Additionally, it is designed to operate without a fan or electricity. Unit includes a standard 20' hose.



F-150



F-375

MODEL	F-150	F-375
FUEL TYPE	VAPOR PROPANE	VAPOR PROPANE
BTU/HR	50,000 MIN. 150,000 MAX.	220,000 MIN. 375,000 MAX.
CFM	N/A	OPTIONAL
POWER REQUIREMENTS	N/A	N/A
FUEL CONSUMPTION	0.54 TO 1.63 GAL/HR	2.39 TO 4.09 GAL/HR
IGNITION	MANUAL	MANUAL
MANIFOLD PRESSURE	2-1/4 TO 20 PSI	7 TO 20 PSI
AIR OUTLET DIA.	8"	13"
L x W x H	30" x 11.25" x 14"	42" x 17" x 22"
WEIGHT	32 LBS	65 LBS
OPTIONAL FAN	--	800 CFM FAN ASSEMBLY (120V)
OPTIONAL MANIFOLD	2 CYLINDER (2001-S2) OR 3 CYLINDER (2001-S3)	2 CYLINDER (2001-S2) OR 3 CYLINDER (2001-S3)

**LIGHT
AND
HIGHLY
MOBILE
DESIGN**