



flagro[™]
USA INC.

FVO-1100TR

SELF-CONTAINED HEATER TRAILERS

TURNKEY PORTABLE HEAT AND POWER

Flagro self-contained heaters work well for remote applications that require heat where a jobsite power source is unavailable. Standard features include a solid steel welded channel frame and floor, electric emergency second axle brakes, as well as safety chains, ball, or pintle hitch and jack.

FEATURES

Diesel Engine

Engine features include electric start/glow plugs, battery charging alternator, heavy duty radiator, and air cleaner.

Built-In Generator

Generator is single phase, 120V, contains instrument panel (with keyed ignition and hour meter), and 8 kW at 1,800 RPM (14HP).

On-Board Fuel Tank

Fuel tank is a TC approved steel tank with 2" fuel inlet nozzle mounted at the side of the trailer for ground access.



FVO-400TRLT

MODEL	FVO-1000TR	FVO-1100TR	FVO-400TRC (NO LIGHT TOWER) FVO-400TRLT (LIGHT TOWER)
ENGINE	YANMAR OR KUBOTA LIQUID COOLED DIESEL	YANMAR OR KUBOTA LIQUID COOLED DIESEL	YANMAR OR KUBOTA LIQUID COOLED DIESEL
HEATERS	(2) FVO-400HC FLAGRO INDIRECT FIRED HEATERS	(2) FVO-400RC FLAGRO INDIRECT FIRED HEATERS	(1) FVO-400RC FLAGRO INDIRECT FIRED HEATERS
FUEL CONSUMPTION	ENGINE: 1.08 GAL/HR AT FULL LOAD HEATERS: (2) 400,000 BTU AT 2.75 GAL/HR	ENGINE: 1.08 GAL/HR AT FULL LOAD HEATERS: (2) 400,000 BTU AT 2.75 GAL/HR	ENGINE: 1.08 GAL/HR AT FULL LOAD HEATERS: (1) 400,000 BTU AT 2.75 GAL/HR
RUN TIME	44 HRS	44 HRS	78 HRS
GENERATOR	STAMFORD NEWAGE	STAMFORD NEWAGE	STAMFORD NEWAGE
FUEL TANK*	300 GALLONS	300 GALLONS	300 GALLONS
BURNER TECHNOLOGY	RIELLO BURNER	RIELLO BURNER	RIELLO BURNER
L x W x H	15' x 7'4" x 7'	15' x 7'4" x 7'	12' x 7'4" x 7'
WEIGHT	4,300 LBS (EMPTY)	4,300 LBS (EMPTY)	2,900 LBS (EMPTY)
APPROVALS	CSA & ESA APPROVED DOT APPROVED TRAILER	CSA & ESA APPROVED DOT APPROVED TRAILER	CSA & ESA APPROVED DOT APPROVED TRAILER

*TRANSPORT CANADA APPROVED